

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04L 12/56, H04M 7/06		A1	(11) International Publication Number: WO 00/33519
			(43) International Publication Date: 8 June 2000 (08.06.00)
(21) International Application Number: PCT/US99/26894		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 12 November 1999 (12.11.99)			
(30) Priority Data: 60/110,398 1 December 1998 (01.12.98) US 60/132,552 5 May 1999 (05.05.99) US			
(71)(72) Applicant and Inventor: SIMON, Thor [US/US]; 21 West Street #3k, New York, NY 10006 (US).			
(74) Agent: OPPEDAHN, Carl; Oppedahl & Larson LLP, P.O. Box 5270, Frisco, CO 80443-5270 (US).			

Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: IMPROVED SIGNALING SYSTEM FOR TELECOMMUNICATIONS

(57) Abstract

A pair of devices (400, 401) appear to be a Common Channel Signaling (CCS) network nodes on each end of a point-to-point digital data link, that is, a normal CCS signaling link (402, 403). Multiple transport methods may be used to provide a redundant and diverse path for the signaling link. These methods include the encapsulation of the CCS protocol, at one or more layers, within other network protocols. In another embodiment, the present invention implements a virtual Signal Transfer Point by means of one or more encapsulating STPs (eSTPs). A packet data network (408) using standard packet-switched data protocols, rather than a backplane bus or special-purpose network, connects the encapsulating STPs (405, 406), and CCS messages are dynamically routed across the internal packet data network to an appropriate eSTP for transmission to the appropriate next hop address. The entire group of eSTPs appears to be one STP to the CCS network, but on the internal packet data network each eSTP operates as an autonomous message router for CCS traffic.

